

8008 FLUSHING OIL



Textiles

DESCRIPTION

Fluid, pale oil.

APPLICATIONS

For routine cleaning and flushing of circular latch needle knitting machines.

APPLICATION DETAILS

8008 FLUSHING OIL should be used as supplied by applying it to the needles and cam tracks. In the case of heavy contamination, it is recommended that a quantity of waste fabric is knitted after applying the flushing oil.

The machine should be thoroughly re-oiled with normal quality needle lubricant after flushing with 8008 FLUSHING OIL.

PERFORMANCE DATA

- The low viscosity ensures easy penetration into the various knitting elements.
- The oil helps to soften, loosen and remove deposits of dirt, fibre, swarf and oxidized oil from the knitting elements, and therefore assisting in clean running of the knitting machine.
- Non-corrosive to the metals normally used in textile machinery.
- When used for flushing sock knitting machines with circulatory oil-feed, it is recommended that the oil return pipe is first disconnected, running the flushing oil to waste.

TYPICAL CHARACTERISTICS AND PROPERTIES

8008 FLUSHING OIL	UNITS	TYPICAL RESULT
Colour		Fluid, pale oil
Viscosity @ 21°C	cSt	Approx. 6
Density @ 15°C	kg/l	Approx. 0.825
Flash Point (SETA)	°C	> 125
Ionic Character		Non-ionic
Emulsifiability		Self-emulsifiable in water
Shelf Life		7 years in original container stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other application.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: techserv@vickers-oil.com

Accredited to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717