


**DC88**

**DOUBLE CYLINDER**

**DC88 E1360X - DC88 E1460X - DC88 E1560X**

# DOUBLE CYLINDER

DC88 E1360X - DC88 E1460X - DC88 E1560X





All images in this brochure are indicative and not binding.

## DOUBLE CYLINDER

### DC88 E1360X - DC88 E1460X - DC88 E1560X

Double cylinder single-feed high speed machine for the production of men's, women's and children's socks in ribs, plain knit and links. Needle-needle single-magnet selection for several rib and links patterns. Tuck knitting option on lower cylinder. Brushless motor incorporated in the column with variable heel and toe reciprocating motion. 2 selection points instead of pickers and needle droppers. Electronic size control by automatic adjustment of the stitch. Available in 3" 1/2, 3" 3/4 and 4" diameters and gauge from 7 to 22.

- Needle-needle single-magnet selection instead of pickers and needle droppers and links drums for different rib and links patterns.
- Simplified shell/skirt with less mobile cams
- Takedown with electronic control and size self adjustment
- Stitch cams with independent stepper motors
- Electronic full control of yarnfingers and of all functions
- Easier sinkers maintenance thanks to the rotating knitting head

#### DIMENSIONS



Length cm 90  
Depth cm 104 + yarn creel cm 60  
Height cm 260

#### WEIGHT



Machine ca. 330 Kg  
Yarn creel ca. 24 Kg

#### CERTIFICATION



Green  
Label

# DOUBLE CYLINDER

## DC88 E1360X - DC88 E1460X - DC88 E1560X

### TECHNICAL FEATURES

MODEL	CYLINDER DIAMETER	GAUGE	NEEDLE THICKNESS
DC88 - E1360X	3"1/2	da 9 a 22	0.5 - 0.6 - 0.7 mm
DC88 - E1460X	3"3/4	da 9 a 22	0.5 - 0.6 - 0.7 mm
DC88 - E1560X	4"	da 7 a 22	0.5 - 0.6 - 0.7 - 0.9 mm

Above data are indicative and not binding.

### STANDARD DEVICES

- Needle-needle single-magnet electronic selection system;
- Sock downtake with downwards movement control;
- Automatic turning device;
- Multi-stiffening by means of stepper motor;
- High heel by means of single-magnetic selection;
- Sinker cap with internal lubrication;
- 6 pneumatic yarnfingers;
- 4-rod take-up device;
- Suction valve controlled with stepper motor;
- Tail knitting at the start of the sock;

### OPTIONAL DEVICES

- Fan
- Picot welt
- Size electronic control
- Split device
- Pneumatic yarnfinger number 7
- First yarnfinger positioning at feeds 5,6 and 7
- Second yarnfinger positioning at feeds 2,3 and 4
- Lycra plating
- Bare Lycra
- 6-rod take-up device
- Yarn brake discs opener 1 and 2
- Prearrangement for YoYo feeder
- Prearrangement for LGL feeder
- Spyder sensors
- Cassefils mechanical sensors
- Knots electric sensors
- Ethernet board
- Air Booster prearrangement

### SUITABLE YARNS

The machine is designed to be used with the following yarns

- Natural fibers
- Syntetic yarn
- Elastic yarn

### POSSIBLE KNITTING

The standard machine can perform the following knittings

- Plain knit
- Rib
- Links
- Tuck stitch on lower cylinder

## NUMBER OF COLORS

Number of colors

1 color on the same course  
Up to 5 colors on first feed

## PERFORMANCES

		4" CYLINDER DIAMETER
GAUGE		14 (needle thickness 0.7)
		LINKS = 360 Rpm
KNITTING FEATURES		Rib and plain knit = 400 Rpm
		Tuck stitch = 260 Rpm
		Reciprocated motion = 380 Rpm

Above data are indicative and not binding.

## GAUGE

		GAUGE															
Model	∅	6	7	8	9	10	11	12	13	14	15	16	17	18	20	22	
1360X	3 1/2"				96	108	116	128	140	152	160	172	184	196	216	240	
					100	112	120	132	144	156	164	176	188	200	220	224	
					104		124	136	148			168	180	192			
		Needle thickness 0.7															
Needle thickness 0.6																	
Needle thickness 0.5																	

		GAUGE															
Model	∅	6	7	8	9	10	11	12	13	14	15	16	17	18	20	22	
1460X	3 3/4"				104	112	124	136	148	160	172	184	196	208	232		
					108	116	128	140	152	164	176	188	200	212	236		
						120	132	144	156	168	180	192	204	216	240		
		Needle thickness 0.7															
Needle thickness 0.6																	
Needle thickness 0.5																	

		GAUGE															
Model	∅	6	7	8	9	10	11	12	13	14	15	16	17	18	20	22	
1560X	4"	70	84	96	108	120	132	148	160	172	184	196	208	220	248		
		80	88	100	112	124	136	152	164	176	188	200	212	224	252		
			92	104	116	128	140	156	168	180	192	204	216	228	256		
							144								232		
Needle thickness 0.9																	
Needle thickness 0.7																	
Needle thickness 0.6																	
Needle thickness 0.5																	

Above data are indicative and not binding.

### DISCLAIMER:

For gauges lower or higher than those in the chart, their maximum speed must be reduced by 10-15%. Should you use staple fiber, maximum speed has to be detected each time according to the yarn and the item to be produced.



**LONATI SPA**

Via Francesco Lonati, 3 | 25124 Brescia (Italy)  
Tel. +39 030 23901 | Fax +39 030 2310024  
C.F.: 01469680175 | P.iva: 02096730961  
info@lonati.com - www.lonati.com