


GOAL
SINGLE CYLINDER
GK616D - GK516D

SINGLE CYLINDER

GK616D - GK516D




KNITTING HEAD
designed to knit high quality items and ensure constant reliability over time.

SINKERS CAP
selected terry

NEW ELECTRONICS
with high resolution touch screen display

NEW BASE
designed to increase solidity and rigidity, allows a more ergonomic assembling of components

* The image refers to the closed toe version



All images in this brochure are indicative and not binding.

SINGLE CYLINDER GK616D - GK516D

1 feed machines are the best sellers of the Goal Line as, thanks to their versatility, they can produce several different items, from the very simple to the most complex, without compromising on quality and efficiency. Available in different diameters and numbers of needles. Latest generation electronics provides control and execution of all machine commands. Drawings and articles are created and managed by Digraph 3 Plus software package, which contains a full collection of styles the operator can combine in different ways to obtain the desired results.

- 6 colors pattern on course, selected terry or plain knit. selected terry also on reciprocating areas
- Reciprocated heel and toe in different sizes and 3D effects
- 28 yarn fingers
- Rising dial and finger plate with stepping motor
- 9 electronic actuators for needle selection plus 1 electronic actuator for sinker selection
- Brushless coaxial main motor

DIMENSIONS



Length cm 85,8
Depth cm 103,7
Height cm 180

WEIGHT



Machine ca. 230 Kg
Yarn creel ca. 46 Kg

CERTIFICATION

SINGLE CYLINDER

GK616D - GK516D

TECHNICAL FEATURES

MODEL	CYLINDER DIAMETER	GAUGE	NEEDLE THICKNESS
GK616D	3"3/4	da 7 a 17	0.85 - 0.70 - 0.60 mm
GK516D	4"	da 6 1/2 a 16	0.85 - 0.70 - 0.60 mm

Above data are indicative and not binding.

STANDARD DEVICES

- Stepper motor electric dial with adjustable height
- Stitch cam feed: 1 with 3 different heights.
- Selected terry motorized sinkers cap for sinker pressure and angular position
- High resolution touch screen display
- Yarn sliding sensors guard cleaning device
- Heel yarn recover device with four positions
- 9 yarnfingers on stitch feed
- Yarn creel
- USB port
- 18 color yarnfingers
- Circular yarn cutter with mechanical stop
- 1 yarnfinger on laid-in elastic feed
- Stepper motor controlled adjustable suction valve

MAIN OPTIONAL DEVICES

- LGL Eco Power or Compact yarn storage feeder
- Dinema YoYo positive yarn feeders
- Elastic yarn positive feeders, for compression socks
- Dinema Plus elastane positive feeders
- Motorized stitch cams
- Antitwist device
- Footlet device
- G-Flot device
- G-Flot 2 device
- Elastane extra tweezers device
- Yarn recover device, 6 positions
- Yarn trimming circular cutter with adjustable speed
- Ethernet board for connection to Dinema Nautilus data collector system
- second elastic yarnfinger
- Yarn sliding control sensors, Dinema ISPY
- Pneumatic yarn tensioner for covered elastane
- Suction fan

POSSIBLE KNITTING

The standard machine can perform the following knittings

- 6 colors pattern plus ground color, mesh, tuck and float stitch, plain knit or terry
- With laid-in elastic: 6 colors pattern plus ground color, tuck and float stitch, plain knit or plating selected terry
- With laid-in elastic: 5 colors pattern plus ground color, mesh, tuck and float stitch, plain knit or plating selected terry

NUMBER OF COLORS

Number of colors

6 on course plus ground

PERFORMANCES

		3" 3/4 4" CYLINDERS
KNITTING FEATURES		Patterns or selections or terry 250 rpm
		Plain knit without pattern, high speed sinker cap 250 rpm.
MAXIMUM SPEED		250 rpm

Above data are indicative and not binding.

DISCLAIMER: maximum speed may vary depending on yarn, knitting, lubrication etc

GAUGE

		GAUGE																					
Model	ø	6½	7	7½	8	8½	9	9½	10	10½	11	11½	12	12½	13	13½	14	14½	15	15½	16	16½	17
GK516DF	4"	84	88	86		108 112		116 120		128 132	136	144		156 160		168	176	180	188	192	200		
		Needle thickness 0.85 mm																					
		Needle thickness 0.70 mm												Needle thickness 0.60 mm									
GK616DF	3"3/4		84	88	86		108	112	116	120 128	132		144		156	160	168		176	180	188	192	200
		Needle thickness 0.85 mm																					
		Needle thickness 0.70 mm															Needle thickness 0.70 mm						

Above data are indicative and not binding.

DISCLAIMER:

All features in the brochure are for information only and subject to change without any prior notice.

For a complete list of available options, please contact Lonati sales network.
The Company accepts no liability for improper use of machinery.



LONATI SPA

Via Francesco Lonati, 3 | 25124 Brescia (Italy)
Tel. +39 030 23901 | Fax +39 030 2310024
C.F.: 01469680175 | P.iva: 02096730961
info@lonati.com - www.lonati.com