

JENILUBE 22



DESCRIPTION

Clear, pale yellow needle lubricant with a mild odour.

APPLICATIONS

Designed for use in circular and flatbed knitting machines, knitting synthetic yarns or other goods which will not be scoured.

APPLICATION DETAILS

JENILUBE 22 can be applied by any of the normal methods including automatic lubricators (either drip feed or spray type) or by oil can application or brushing.

PERFORMANCE DATA

- Resistant to oxidation; does not form sticky resinous deposits.
- Provides good lubrication.
- Not self emulsifiable but is readily removed from textured polyester and textured polyamide yarns together with the normal emulsifiable yarn lubricant using mild detergent and alkali scours.
- Suitable for use in knitting dyed goods which will not be subject to scouring.

NOTES

When introducing a new oil to a machine we recommend cleaning the original oil from the machine and oiler unit as thoroughly as possible, to avoid the potential of any incompatibility problems.

TYPICAL CHARACTERISTICS AND PROPERTIES

JENILUBE 22	UNITS	TYPICAL RESULT
Colour		Clear pale yellow
Viscosity @ 40°C	cSt	22
Density @ 15°C	kg/l	0.849
Flash Point (SETA)	°C	> 180
VI		105
Emulsifiability		Not self emulsifiable; but readily scoured using mild detergent and alkali
Shelf Life		7 years in original container stored out of direct sunlight

Vickers Oils, its officers, employees and agents assume no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with Vickers Oils for the provision of this information or advice and in that case responsibility or liability is exclusively on the terms and conditions set out in that contract. Products should only be used for the applications specified. The supplier cannot accept responsibility if they are used in any other application.

BENJ^N R. VICKERS & SONS LTD.

Registered Office
6 Clarence Road, Leeds,
LS10 1ND, United Kingdom

Registered in England
Company No. 00130013

Tel: +44 (0) 113 386 7654
Fax: +44 (0) 113 386 7676
Web: www.vickers-oil.com
Email: techserv@vickers-oil.com

Accredited to the ISO 9001
Quality Standard and the
ISO 14001 Environmental
Management Standard



FM 01851 EMS 40717